

Approved For Release 2002/06/14 : CIA-RDP69B00404R000100070003-5

DATE

SECRET

ROUTING

1	RID	9
2		10
3		11
4		12
5	OXL	13
6	"	14
7		15
8		16

TO :  
FROM :  
ACTION:  
INFO :

CHIEF  
D/CHIEF  
OPS  
PLANS

HOLD FOR:

T.H.

FILE

IN 92799

20-22(6)

OSA 20 70

TO

INFO

CITE

SECRET 080117Z CITE 1466

PRIORITY

OXCAR

SUBJECT: EVALUATION OF BLACK SHIELD MISSION BX6710

1. CAMERA F, TYPE I, WAS USED ON MISSION BX6710. THE EXPOSURE WAS GOOD. PROCESSING WAS ACCOMPLISHED AT [REDACTED]. THERE IS A TOTAL OF 1480 FRAMES.

2. BOTH CAMERAS OPERATED SATISFACTORILY THROUGHOUT THE MISSION. DURING STRAIGHT AND LEVEL FLIGHT, GROUND RESOLUTION OF 18 INCHES (ONE BAR PLUS ONE SPACE) WAS OBTAINED IN THE VERTICAL PORTIONS OF THE PHOTOGRAPHY. METERING WAS SATISFACTORY WITH OVERLAP OCCURRING ONLY AT STARTUP OR RUNDOWN.

3. THERE WAS NO CAMERA OPERATION DURING ASCENDING AND DESCENDING PORTIONS OF THE MISSION. ALTITUDES RANGED FROM 75,100 FEET TO 80,900 FEET (UNCORRECTED BAROMETRIC READINGS).

4. EXPOSURE WAS 1/190 FOR THE FIRST 1,340 FRAMES AND 1/170 FOR THE REMAINDER OF THE MISSION. THE ENTIRE MISSION WAS PROCESSED AT FULL.

SECRET

GROUP 1  
EXCLUDED FROM AUTO-  
MATIC DOWNGRADING  
AND DECLASSIFICATION

25X1A IN 92799   1466 S E C R E T PAGE 2

5. A GOOD CORRELATION WAS OBTAINED. THE TIME FROM THE FILM DATA BLOCK WAS ONE SECOND HIGHER THAN THE INS ELAPSED TIME THROUGHOUT THE MISSION THE INS TAPE IS SATISFACTORY.

6. THE ELAPSED TIME OF EVENTS AFTER VEHICLE LANDING IS AS FOLLOWS:

	HOURS	MINUTES
INS TRANSMISSION RECEIVED	01	42
D VALUE CABLE RECEIVED	09	42
MATERIAL ARRIVED <span style="border: 1px solid black; padding: 0 20px;"> </span>	25	03
UNTITLED DP'S ARRIVED AT NPIC	35	33
FINAL FRAME EPHEMERIS COMPLETED	38	48
INITIAL READOUT COMPLETED	47	33
IPIR SENT FROM <span style="border: 1px solid black; padding: 0 20px;"> </span>	49	33

7. APPROXIMATELY 50 PERCENT OF THE MISSION IS IN THE CAGED STATUS. MOST OF THE CAGING OCCURRED DURING TURNS. THE DATA BLOCK CAGING LIGHT DISAGREED WITH THE INS INDICATOR FOR A TOTAL OF SIX FRAMES. MOST OF THE MISSION USED PROGRAMMED V/H. THE FOLLOWING IS A TABLE SHOWING THE ERROR IN THE V/H.

FRAME	PERCENT CLOUD COVER AT ZERO SCAN	V/H INDICATOR	INS V/H	APLUSB PERCENT OVERLAP	PERCENT ERROR IN V/H
287-289	0	CN	0.0397	3.36	6.19
331-333	5	CN	0.0400	3.32	4.78
341-343	5	CN	0.0400	3.29	3.75
533-535	0	CN	0.0397	3.23	1.77
605-607	5	CN	0.0397	3.31	3.61
711-713	5	CN	0.0390	3.13	-1.40
759-761	0	CN	0.0395	3.25	2.42
1077-1079	5	OFF	0.0403	3.32	4.78
1397-1399	5	CN	0.0392	3.26	2.75
1429-1431	5	OFF	0.0399	3.29	3.75

8. CLOUDS COVERED APPROXIMATELY 30 PERCENT OF THE MISSION. LIGHT HAZE WAS EVIDENT THROUGHOUT.

S E C R E T TOR: 080137Z AUG 67

S E C R E T